



Representative Image

## Catalog No. 1SVR405618R1400

**Description:** CR-M024DC4LDG Pluggable interface relay 4c/o,A1-A2=24VDC,gold contacts,diode,LED

**UPC No** 4013614497988

**Home > Controls & Protective Relays > Interface Relays & Optocouplers**

### Descriptors

|          |                                 |
|----------|---------------------------------|
| Category | Interface Relays & Optocouplers |
|----------|---------------------------------|

### Specifications

|                              |                                                                                    |
|------------------------------|------------------------------------------------------------------------------------|
| Function                     | Pluggable miniature interface relay CR-M                                           |
| Rated Control Supply Voltage | 24 V DC                                                                            |
| Output Signal                | 250 V / 6 A                                                                        |
| Output                       | 4 c/o (SPDT) contacts                                                              |
| Contact material             | silver-nickel alloy gold plated (AgNi/Au)                                          |
| Product Main Type            | CR-M                                                                               |
| Sub-Function                 | Relay with built in LED<br>Relay with built in LED, diode and gold-plated contacts |
| RoHS Status                  | Following EU Directive 2011/65/EU                                                  |
| Object Classification Code   | K                                                                                  |

### Classifications

|          |                            |
|----------|----------------------------|
| ETIM 4   | EC001437 - Switching relay |
| ETIM 5.0 | EC001437 - Switching relay |
| ETIM 6.0 | EC001437 - Switching relay |
| ETIM 7   | EC001437 - Switching relay |
| eClass   | 7.0 27371601               |

### Dimensions

|                            |         |
|----------------------------|---------|
| Product Net Width          | 21.2 mm |
| Product Net Height         | 35.6 mm |
| Product Net Depth / Length | 27.5 mm |
| Product Net Weight         | 0.033kg |

### Package Information

|                       |          |
|-----------------------|----------|
| Package Level 1 Units | 10 piece |
|-----------------------|----------|

**by ABB**

### Package Information

|                                |               |
|--------------------------------|---------------|
| Package Level 1 Width          | 114 mm        |
| Package Level 1 Height         | 61 mm         |
| Package Level 1 Depth / Length | 50 mm         |
| Package Level 1 Gross Weight   | 0.35 kg       |
| Package Level 1 EAN            | 4013614401022 |

### Ordering

|                        |                                          |
|------------------------|------------------------------------------|
| Minimum Order Quantity | 10                                       |
| Customs Tariff Number  | 85364900                                 |
| ECCN                   | N                                        |
| ECN                    | N                                        |
| ABB MDF Code           | 3DL - Relays (LV / Control + Protection) |
| ABB Business Unit      | ELSP - Smart Power                       |