



Representative Image

Catalog No. 1SVR740774R3300

Description: CM-PAS.41P Three-phase monitoring relay 2c/o, 0,0.1-30s, L1-L2-L3=3x300-500VAC

UPC No 4016779851985

Home > Controls & Protective Relays > Measuring & Monitoring Relays

Descriptors

Category	Measuring & Monitoring Relays
----------	-------------------------------

Specifications

Product Line Type	Three-Phase Monitoring Relays
Function	Phase failure detection Phase sequence monitoring Phase unbalance detection
Output	2 c/o (SPDT) contacts
Rated Control Supply Voltage	(L-L) 300 ... 500 V AC
Measuring Range	(L-L) 300 ... 500 V AC
Terminal Type	Screwless Terminals
Product Main Type	CM-PAS
Time Range	200 ms start-up delay 0 s or 0.1 ... 30 s tripping delay (ON)
Ambient Air Temperature	Operation -25 ... +60 °C Storage -40 ... +85 °C
RoHS Status	Following EU Directive 2011/65/EU
Maximum Operating Voltage UL/CSA	Output Circuit 300 V AC
Contact Rating UL/CSA	B300
Connecting Capacity UL/CSA	Flexible 2x 18-16AWG Rigid 2x 20-16 AWG
Object Classification Code	B

Classifications

ETIM 4	EC001441 - Phase monitoring relay
ETIM 5.0	EC001441 - Phase monitoring relay
ETIM 6.0	EC001441 - Phase monitoring relay
ETIM 7	EC001441 - Phase monitoring relay
eClass	7.0 27371803

Dimensions

Product Net Width	22.5 mm
Product Net Height	85.6 mm

by ABB

Dimensions	
-------------------	--

Product Net Depth / Length	103.7 mm
Product Net Weight	0.123 kg

Package Information	
----------------------------	--

Package Level 1 Units	1 piece
Package Level 1 Width	97 mm
Package Level 1 Height	109 mm
Package Level 1 Depth / Length	30 mm
Package Level 1 Gross Weight	0.148 kg
Package Level 1 EAN	4016779851985

Ordering	
-----------------	--

Minimum Order Quantity	1
Customs Tariff Number	85364900
ECCN	N
ECN	N
ABB Business Unit	ELSP - Smart Power
ABB Product Group	3099>>ELSP