



Representative Image

## Catalog No. 9T10A1077

**Description:** 3A,225KVA,480-380Y,150C,N2,K1,DOE

**UPC No** 783173902523

**Home > Transformers > Dry Type Vented > General Purpose**

ABB Low-Voltage General Purpose Dry-Type transformers are built to last more than 20 years and are UL Listed. Our Type QL & QF transformers meet DOE 2016 efficiency standards and are UL Energy Verified as energy efficient. They are available with aluminum or copper windings and in all three temperature rise ratings. Quiet Performance-Core and coil assemblies are mounted on rubber isolation pads to reduce noise. Single-piece front/back is easily removable for installation and service. Qualified to the seismic requirements of IEEE-693-2005 and IBC-2021 and CBC 2022.

### Descriptors

|          |                 |
|----------|-----------------|
| Category | General Purpose |
|----------|-----------------|

### Specifications

|                  |          |
|------------------|----------|
| TransType        | DOE 2016 |
| Phase            | 3        |
| PriVoltage       | 480      |
| SecVoltage       | 380Y/219 |
| KVA              | 225 KVA  |
| Coil Material    | AL       |
| TempRise         | 150 °C   |
| Frequency        | 60 Hz    |
| AmbTemp          | 40 °C    |
| EnergyEfficiency | DOE 2016 |
| KFactor          | K1       |
| Enclosure Type   | NEMA 2   |
| Sound            | Std      |

### Classifications

|    |     |
|----|-----|
| UL | Yes |
|----|-----|