



Representative Image

Catalog No. 2TLA020007R3400

Description: JSTD1-E SAFEBALL 1NO+1NO

UPC No 7350024460223

Home > Machine Safety > Safety Control Devices

JSTD1-E Safeball, 2 NO, 0.2m wires x 4 for direct connection into an enclosure. Ergonomic design with several grip possibilities and low activation force (approx. 2N) and flexible mounting options. Provides highest level of safety for use in two hand control applications when using two Safeballs in conjunction with appropriate safety relay or Pluto Safety PLC. Maximum load of 30VDC, 2A resistive, IP67 protection degree, plastic body.

Descriptors

Category	Safety Control Devices
Type	One/Two Hand Control Device

Specifications

Product Class	One and Two Hand Control Devices
Product Main Type	JSTD1
Supply Voltage	24VDC
Degree of Protection	IP67

Classifications

ETIM 4	EC002611 - Control switch
ETIM 5.0	EC002611 - Control switch
ETIM 6.0	EC002611 - Control switch
ETIM 7	EC002611 - Control switch
ETIM 8 (Etim8)	EC002611 - Control switch

Dimensions

Product Net Depth / Length	72 mm
Product Net Height	71 mm
Product Net Width	72 mm
Product Net Weight	0.07kg

Safety Information

Performance Level	Up to e
-------------------	---------