

Representative Image

## Catalog No. TH4322SS

**Description: 60A 3P HD N4X SS 240V FUSIBLE**

**UPC No 783164089240**

**Home > Switches & Disconnects > Disconnect & Safety Switches > Safety Switches > Heavy Duty**

When it comes to getting the job done right, you can count on safety switches from ABB. ABB offers a wide variety of general duty switches for residential and light commercial purposes, while the extensive line of heavy-duty switches is best suited for commercial and industrial applications. For the toughest industrial environments — such as cement foundries, steel mills and processing plants — dust-tight and stainless steel switches are available. We also offer a variety of double throw switches for emergency generators. No matter the application, we've got you covered with a rugged, reliable and easy-to-install Spec-Setter safety switch. 60A 3P HD N4X SS 240V FUSIBLE

### Descriptors

| | |
|---|---|
| Category | Heavy Duty |
| GO Schedule | S1 |

### Specifications

| | |
|---|---|
| Voltage | 240 AC |
| Amperage | 60 A |
| Poles | 3 |
| Wires | 4 |
| Fusing | Fusible |
| Enclosure | NEMA 4/4X Water/Dust-tight |
| Options | None |
| Wire Range (Cu/Al) | 14-2 |
| 240 Vac, NEC Std, 1-ph | 3 hp |
| 240 Vac, NEC Std, 3-ph | 7.5 hp |
| 240 Vac, Time Delay, 1-ph | 10 hp |
| 240 Vac, Time Delay, 3-ph | 15 hp |
| 250 Vdc | 10 hp |
| GSA Compliance | Yes |

### Classifications

| | |
|---|---|
| cUL Listed | Yes |
| UL Listed | Yes |

### Dimensions

| | |
|---|---|
| Height | 19.30 in |
| Width | 9.40 in |
| Weight | 23 lb |

by ABB