Representative Image

Catalog No. TM42415C

Description: 150A 42CRT 3P4W 208Y/120V 10KIC CMB

UPC No 783164190038

Home > Load Center & Meter Combos > Load Centers

Main breaker load centers arrive with a main breaker installed for a convenient and swift install. Main breakers allow for the user to stop the flow of electricity in the load center, shutting off all the power in the residence. The TM42415C features spaces for 40, 1" breakers, a 150A main ampere rating, 3 phases, and a combination surface/flush enclosure.

Descriptors

Category	Load Centers
GO Schedule	R7

Specifications

# Branch Circuit 250A	42
1" Space	42
1/2" Space	0
Amperage	150 A
Circuit Breaker Style	Plug-In
Device type	Main Breaker
Door	Yes
Enclosure	Indoor
Enclosure Type	Indoor, Combination
Factory Installed Ground Kit	No
Feed	Top
Input/Output Voltage	208Y/120V ac
Interrupting Capacity Rating	22
Load Center Type	Standard
NEMA Rating	NEMA 1
Phase	3 Phase
Service & Voltage	3 Phase, 4 Wire, 208Y/120V ac
Wires	4 Wire

Classifications

UL/CUL Listing	UL

Dimensions

Height	39.2 in
Weight	40.4 lb
Width	14.0 in

by ABB