



Image coming soon

Part Number : [1201150043](#)
Product Description : M12 Signal, A-Coded, MPIS
Passive Distribution Box, Side Mount, 3 Poles, 8 Ports,
NPN LED Indicators, PVC Home Run Cable, 5.0m (16.4')
Length
Series Number : 120115
Status : Active
Product Category : Passive Distribution Boxes
Engineering Part Number : 803N801

Documents and Resources

Drawings
[1201150043_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Reviewed per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2025)7771-DC (04 Feb 2026)
EU RoHS	Compliant per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	Passive Distribution Boxes
Series	120115
Description	M12 Signal, A-Coded, MPIS Passive Distribution Box, Side Mount, 3 Poles, 8 Ports, NPN LED Indicators, PVC Home Run Cable, 5.0m (16.4') Length
IP Rating	IP67
Product Name	M12 Signal, Micro-Change (M12), MPIS
UPC	78678824056

Electrical

Current - Maximum per Contact	4.0A per port
Functional Wiring	NPN
Voltage - Maximum	10-30V DC
Wiring Configuration	Single I/O per Port

Physical

Bus I/O	Micro-Change (M12)
Cable Connector Orientation	N/A
Home Run Cable Length	5.0m
Home Run Connector	N/A
Home Run Interface	Cable - Side Entry
Keyway	A-Coded
LED Indicator	NPN Sensors
Material - Cable Jacket	PVC
Material - Housing	PBT

Material - Metal	Copper Alloy
Material - Plating Mating	Gold
Net Weight	1.000/g
Orientation	Side Mount
Poles	5
Poles (wired)	3
Ports	8
Temperature Range - Operating	-25° to +90°C