



Part Number : [1201080042](#)

Product Description : M12 Data, D-Coded, M12 Push-Pull Ultra-Lock Double Ended Cordset, 4 Poles, M12 Ultra-Lock Male (Straight) to Male (Straight), 2x2x26 AWG, Teal Shielded PVC Cable, 1.0m (3.28') Length

Series Number : 120108

Status : Active

Product Category : Industrial Cable Assemblies

Engineering Part Number : EWWA06015M010



Documents and Resources

Drawings

[1201080042 sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	 per SJ/T 11365-2006
EU ELV	Not Relevant
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Not Reviewed per D(2025)7771-DC (04 Feb 2026)
EU RoHS	Not Reviewed per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration

- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Active
Category	Industrial Cable Assemblies
Series	120108
Description	M12 Data, D-Coded, M12 Push-Pull Ultra-Lock Double Ended Cordset, 4 Poles, M12 Ultra-Lock Male (Straight) to Male (Straight), 2x2x26 AWG, Teal Shielded PVC Cable, 1.0m (3.28') Length
IP Rating	IP67
Performance Category	5e
Product Name	M12 Data Push-Pull,Ultra-Lock (M12)
Type	Double Ended
UPC	78172553194

Electrical

Current - Maximum per Contact	1.5A
Voltage - Maximum	30V

Physical

Cable Diameter	6.10mm (.240")
Cable Length	1.0m (3.28')
Color - Cable Jacket	Teal
Connector End A	M12 Data Push-Pull
Connector End B	M12 Data Push-Pull
Coupling Style	Push-Pull

Gender	Male-Male
Keyway	D-Coded
LED Indicator	None
Material - Cable Jacket	PVC
Material - Connector Body	PUR
Material - Contact	Copper Alloy
Material - Coupling Nut	Nickel-plated Brass
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Orientation	90° to Straight
Poles	4
Temperature Range - Operating	-20° to +75°C
Wire/Cable Type	Shielded-Stranded
Wire Size (AWG)	26