



Part Number : [1200740042](#)

Product Description : M12 Signal, C-Coded, Receptacle, 2 Poles, Male, Front Panel Mount, 1/2" -14 NPT Mounting Threads, 0.34mm² (22 AWG), PVC Wires, 0.30m (12.0") Length

Series Number : 120074

Status : Active

Product Category : Industrial Connectors

Engineering Part Number : 7R2006A19A120

Documents and Resources

Drawings

[1200740042_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Not Relevant
China RoHS	Not Relevant
EU ELV	Not Reviewed per 2000/53/EC
Low-Halogen Status	Not Low-Halogen per IEC 61249-2-21
REACH SVHC	Contains Lead per D(2022)4187-DC (10 June 2022)
EU RoHS	Compliant with Exemption 6(c) per EU 2015/863

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474

- [chemSHERPA \(xml\)](#)

Substances of Interest

- [PFAS](#)

EU RoHS Certificate of Compliance

Additional Product Compliance Information

CE - Declaration of Conformity

UKCA - Declaration of Conformity

Part Details

General

Status	Active
Category	Industrial Connectors
Series	120074
Description	M12 Signal, C-Coded, Receptacle, 2 Poles, Male, Front Panel Mount, 1/2" -14 NPT Mounting Threads, 0.34mm ² (22 AWG), PVC Wires, 0.30m (12.0") Length
IP Rating	IP67
NEMA Rating	NEMA 6
Product Name	M12 Signal, Micro-Change (M12)
Type	Single Ended (pigtail)
UPC	78678822668

Agency

CSA	LR6837
UL	E152210

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Coupling Type	External Thread
Gender	Male
Keyway	C-Coded

Length	0.30m
Material - Component	Gray Annodized Aluminum
Mounting Thread Size	1/2" - 14 NPT
Net Weight	125.000/g
Orientation	Straight
Panel Mount	Front
Poles	2
Temperature Range - Operating	-20° to +80°C
Wire/Cable Type	Leads, UL 1061
Wire Size (AWG)	22

This document was generated on Sep 18, 2026