Part Number : 1200730346
Product Description : M12 Signal, C-Coded, Double-Ended Cordset, 5 Poles, Female (Straight) to Male (90°), 18 AWG, Yellow Shielded PVC Cable, Yellow Overmold, 0.91m (3.0') Length
Series Number : 120073
Status : Obsolete
Product Category : Industrial Cable Assemblies
Engineering Part Number : 775032A03F030



Obsolete

Documents and Resources

Drawings

1200730346_sd.pdf

Product Environment Compliance

Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Compliance Statements
- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents
- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest
- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Obsolete
Category	Industrial Cable Assemblies
Series	120073
Description	M12 Signal, C-Coded, Double-Ended Cordset, 5 Poles, Female (Straight) to Male (90°), 18 AWG, Yellow Shielded PVC Cable, Yellow Overmold, 0.91m (3.0') Length
IP Rating	IP67
Product Name	M12 Signal,Micro-Change (M12)
Type	Double Ended
UPC	78678838955

Agency

CSA	LR6837
UL	E152210

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Cable Diameter	7.16mm (.282")
Cable Length	0.91m (3.0')
Color - Cable Jacket	Yellow
Connector End A	M12 Signal
Connector End B	M12 Signal
Coupling Style	Threaded
Gender	Female-Male
Keyway	C-Coded
LED Indicator	No

Obsolete

Material - Cable Jacket	PVC
Material - Connector Body	PVC
Material - Contact	Copper Alloy
Material - Coupling Nut	Black Epoxy Coated Zinc
Material - O-Ring	Nitrile Rubber
Material - Plating Mating	Gold
Orientation	90° to Straight
Poles	5
Temperature Range - Operating	-20° to +105°C
Wire/Cable Type	UL 2661
Wire Size (AWG)	18

Obsolete