



Part Number : [1200730057](#)

Product Description : M12 Signal, C-Coded, Double-Ended Cordset, 2 Poles, Female (Straight) to Male (Straight), 22 AWG, Yellow Shielded PVC Cable, Yellow Overmold, 0.91m (3.0') Length

Series Number : 120073

Status : Obsolete

Product Category : Industrial Cable Assemblies

Engineering Part Number : 772030D02F030



Documents and Resources

Drawings

[1200730057_sd.pdf](#)

Product Environment Compliance

Compliance

GADSL/IMDS	Product not active
China RoHS	Product not active
EU ELV	Product not active
Low-Halogen Status	Product not active
REACH SVHC	Product not active
EU RoHS	Product not active

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

EU RoHS Certificate of Compliance

Additional Product Compliance Information

Part Details

General

Status	Obsolete
Category	Industrial Cable Assemblies
Series	120073
Description	M12 Signal, C-Coded, Double-Ended Cordset, 2 Poles, Female (Straight) to Male (Straight), 22 AWG, Yellow Shielded PVC Cable, Yellow Overmold, 0.91m (3.0') Length
IP Rating	IP67
Product Name	M12 Signal, Micro-Change (M12)
Type	Double Ended
UPC	78678831197

Agency

CSA	LR6837
UL	E152210

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Cable Diameter	5.08mm (.200")
Cable Length	0.91m (3.0')
Color - Cable Jacket	Yellow
Connector End A	M12 Signal
Connector End B	M12 Signal
Coupling Style	Threaded
Gender	Female-Male

Keyway	C-Coded
LED Indicator	No
Material - Cable Jacket	PVC
Material - Connector Body	TPC
Material - Contact	Copper Alloy
Material - Coupling Nut	Black Epoxy Coated Zinc
Material - O-Ring	Fluoro-elastomer
Material - Plating Mating	Gold
Net Weight	68.213/g
Orientation	Straight to Straight
Poles	2
Temperature Range - Operating	-25° to +105°C
Wire/Cable Type	UL 2661
Wire Size (AWG)	22

This document was generated on Sep 18, 2026