



Part Number : [1200980063](#)

Product Description : PROFIBUS Straight D-Sub to Micro-Change (M12) Double-Ended Cordset, 5 Poles, B-Coded, Male (Straight), 24 AWG. PUR Cable, 2.0m (6.56') Length

Series Number : 120098

Status : Active

Product Category : Industrial Cable Assemblies

Engineering Part Number : BM5S60PP4M020



Documents and Resources

Drawings

[1200980063_sd.pdf](#)

Product Environment Compliance

Compliance

China RoHS	Not Reviewed
EU ELV	Not Reviewed
Low-Halogen Status	Not Reviewed
REACH SVHC	Not Reviewed
EU RoHS	Not Reviewed

Compliance Statements

- EU RoHS
- REACH SVHC
- Low-Halogen

Industry Documents

- IPC 1752A Class C
- IPC 1752A Class D
- Molex Product Compliance Declaration
- IEC-62474
- chemSHERPA (xml)

Substances of Interest

- PFAS

Part Details

General

Status	Active
Category	Industrial Cable Assemblies
Series	120098
Description	PROFIBUS Straight D-Sub to Micro-Change (M12) Double-Ended Cordset, 5 Poles, B-Coded, Male (Straight), 24 AWG. PUR Cable, 2.0m (6.56') Length
IP Rating	IP40, IP67
Product Name	Micro-Change (M12),PROFIBUS
Protocol	EtherNet
Type	Double Ended
UPC	78678886180

Electrical

Current - Maximum per Contact	4.0A
Voltage - Maximum	250V AC/DC

Physical

Cable Diameter	8.00mm (.315")
Cable Length	2.0m (6.56')
Color - Cable Jacket	Violet
Connector End A	D-Sub (9-pin)
Connector End B	Micro-Change (M12)
Coupling Style	Threaded
Gender	Male-Male
Keyway	B-Coded
LED Indicator	None
Material - Cable Jacket	PUR
Material - Connector Body	PUR
Material - Contact	Copper Alloy

Material - Coupling Nut	Gray Anodized Aluminum
Material - Plating Mating	Gold
Orientation	Straight to Straight
Poles	5
Temperature Range - Operating	-20° to +80°C
Wire/Cable Type	Twisted Pair
Wire Size (AWG)	24