


Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经书面授权，否则禁止将此文档及其内容进行传递、复制、利用。交流本文件的内容，侵犯者将为赔偿责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。


未注公差/General tolerances(mm)

0~3	>3~6	>6~10	>10~18	>18~30	>30~50	>50~80	>80~120	>120~180	>180~250	>250~315	>315~400	>400~500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°









Please refer to the 3D model,
for these unmarked dimensions.

ITEM	NAME OF PART	MATERIAL	NOTES
4	Cage	Steel	M4/Zn Plated
3	Current carrier	Copper	Sn Plated
2	Screw	Steel	M4/Zn Plated
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRFT	DATE
02		Cancel EAC lettering	邓梁	2024.10.18

APPD:	李根劳	2024.10.18
CHKD:	马恩开	2024.10.18
DRFT:	邓梁	2024.10.18

A4 mm (inch)

UL 标准/UL Standard:	B	C	D
额定电压/电流/Rated Voltage(V)/Current(A)	600/50	/	600/5
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution	III/3	III/2	II/2
额定电压/电流/Rated Voltage(V)/Current(A)	1000/41	/	/
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8	/	/
螺丝扭矩/Torque Tightening(N• m/Lb.in)	M4, 1.54/14		
线径范围(硬线和软线)/Wire Range(rigid and flexible	22~8 / 0.5~6		
间距/Pitch(mm)/线数范围/Poles	8/01P		
剥线长度/Stripping length(mm)	10~12		
使用温度范围/Operating temperature(° C)	-40~+105		
符合RoHS环保要求/Conform to RoHS	Yes		

DEGSON

MATERIAL: SURFACE/COLOR:

MAT NO./REV: 11020000049-1 / 00.01 MAT STATUS: 批量

NAME

DC6-01P-11-00Z(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200115351	CUSTOMER DRAWING	work	2:1	1/1