

Transfer or duplication of this document as well as the utilization or communication of its contents are prohibited unless explicit authorization is granted. Violations will be liable for compensation. All rights reserved for patent, utility model or designs registrations. 除非经予明确授权，否则禁止将此文件的内容交流、复制、利用、交流本文件的内容，侵犯者将为此承担责任。本公司保留对涉及发明、实用新型和外观专利的所有权利。


未注公差/General tolerances(mm)


0~3	>3~6	>6~10	>10~18	>18~30	>30~50	>50~80	>80~120	>120~180	>180~250	>250~315	>315~400	>400~500	>500	0.1/10
±0.12	±0.18	±0.22	±0.26	±0.31	±0.37	±0.57	±0.80	±0.93	±1.05	±1.15	±1.60	±2.20	±2.50	±2°




	B	C	D
UL 标准/UL Standard:			
额定电压/电流/Rated Voltage(V)/Current(A)	600/85	/	/
IEC 标准/IEC Standard:			
过压类别/Overvoltage Category/污染等级/Pollution Degree	III/3		
额定电压/电流/Rated Voltage(V)/Current(A)	1000/76		
额定脉冲电压(KV)/Rate Impulse Voltage(KV)	8		
线径范围(硬线和软线)/Wire Range(rigid and flexible)(AWG/mm²)	20~4 / 0.5~16,25(Sol)		
间距/Pitch(mm)/线数范围/Poles	12.2/01P		
剥线长度/Stripping length(mm)	18		
使用温度范围/Operating temperature(℃)	-40~+105		
符合 RoHS 环保要求/Conform to RoHS	Yes		









ITEM	NAME OF PART	MATERIAL	NOTES
4	Current carrier	Copper	Sn Plated
3	Spring	Stainless steel	/
2	Button	PA66+GF%	UL94V-0
1	Housing	PA66	UL94V-0

REV	ECN	DESCRIPTION	DRFT	DATE
00		Engraving updates	岑乔枫	2024.07.03

DEGSON

APPD:	李根劳	2024.07.03
CHKD:	马恩开	2024.07.03
DRFT:	岑乔枫	2024.07.03

A4 mm (inch)

MATERIAL: | SURFACE/COLOR:

MAT NO./REV: 11040000069-1 / 00.02 | MAT STATUS: 批量

NAME: DS16-01P-1Y-00Z(H)

DRAWING NO.	TYPE	DRAWING STATUS	SCALE	SHEET
200268473	CUSTOMER DRAWING	已发布	2:1	1/1