

DSDC Hazardous Location - 200 A

SP Ratings

- **Max Amperage & Voltage**
200 A, 250 VDC
- **Current Interruption Capability**
Not for current interrupting
- **Environmental Ratings**
Type 4X
- **Temperature Range**
Min -40°F/Max 104°F
See pg 260 for temps below -15°F.
- **Wiring Capacity**
Based on THHN wire sizes.
DSDC1 Min 14 AWG Max 8 AWG
DSDC3 Min 14 AWG Max 4 AWG
DSDC6 Min 10 AWG Max 2 AWG
DSDC9 Min 4 AWG Max 2/0 AWG
DSDC2 Min 4 AWG Max 4/0 AWG
- **Certifications**
CSA C22.2 No. 182.1-07
CSA C22.2 No. 213-M1987
- **Hazardous Ratings**
Class I, Division 2, Groups ABCD, T6
Class I, Zone 2, IIC

Receptacle (female)



Inlet (male)



Devices rated for hazardous locations are not returnable.

Don't forget to add installation accessories to your order

VOLTAGE	POLARITY		PART #		PART #	
			POLY	METAL	POLY	METAL
DSDC1	130 V/20 A	2P+G	35-14109-HAZ	-	35-18109-HAZ	-
DSDC3	130 V/30 A	2P+G	35-34109-HAZ	-	35-38109-HAZ	-
DSDC6	130 V/60 A	2P+G	35-64109-HAZ	36-64109-HAZ	35-68109-HAZ	36-68109-HAZ
DSDC9	130 V/100 A	2P+G	-	36-94109-HAZ	-	36-98109-HAZ
DSDC2	130 V/200 A	2P+G	-	36-24109-HAZ	-	36-28109-HAZ
DSDC1	250 V/20 A	2P+G	35-14209-HAZ	-	35-18209-HAZ	-
DSDC3	250 V/30 A	2P+G	35-34209-HAZ	-	35-38209-HAZ	-
DSDC6	250 V/60 A	2P+G	35-64209-HAZ	36-64209-HAZ	35-68209-HAZ	36-68209-HAZ
DSDC9	250 V/100 A	2P+G	-	36-94209-HAZ	-	36-98209-HAZ
DSDC2	250 V/200 A	2P+G	-	36-24209-HAZ	-	36-28209-HAZ

Receptacle Options Part

Normally Open Lid Recept # - N0

Metal casings only.

Inlet Options Part

Without Lockout Hole Inlet # -A155

Part Number Example

250 V DSDC6 with no options

DSDC6 Metal recept 2P+G = 36-64209-HAZ

Feature Spotlight – Screw-Type Locking Pawl

Listing Requirement
Users must tighten screw to lock the plug in the mated position



DSDC6 shown

Zone 2/Division 2 DSDC receptacles feature a standard screw-type locking pawl. This required feature allows the user to lock the plug to the receptacle by tightening a screw on the pawl.

For added security, a lockout hole is included on the receptacle that enables the user to insert a 5/16" lock or locking pin to prevent the plug from being disconnected or to lock the receptacle lid closed.

5/16" hole for added security

See pages 237-246 for detailed information on these options



INSTALLATION ACCESSORIES

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.

! Accessories rated for hazardous locations are not returnable.



Poly Handle



Poly Handle

For Zone 2 DSDC dimensions use the cross reference chart below and refer to DS dimensions on pgs 55-56.

HANDLES

	CABLE RANGE	POLY HANDLE	1/2"	3/4"	1"	1 1/4"	1 1/2"
DSDC1	.196-.826"	552P0D21	552P0N05	552P0N07	552P0N10	552P0N12	-
DSDC3	.390-1.180"	553P0D30	553P0N05	553P0N07	553P0N10	553P0N12	-
DSDC6	.511-1.377"	554P0D35	554P0N05	554P0N07	554P0N10	554P0N12	554P0N15



Metal Handle

DSDC1, 3, 6 shown



Metal Handle

DSDC9, 2 shown

DIMENSIONS	
DSDC1	same as DS20
DSDC3	same as DS30
DSDC6	same as DS60
DSDC9	same as DS100
DSDC2	same as DS200

	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"	3"
DSDC1	5K2P0N05	5K2P0N07	5K2P0N10	5K2P0N12	-	-	-	-
DSDC3	5K3P0N05	5K3P0N07	5K3P0N10	5K3P0N12	-	-	-	-
DSDC6	5K4P0N05	5K4P0N07	5K4P0N10	5K4P0N12	5K4P0N15	-	-	-
DSDC9	-	5K5P0N07	5K5P0N10	5K5P0N12	5K5P0N15	5K5P0N20	-	-
DSDC2	-	-	5K6P0N10	5K6P0N12	5K6P0N15	5K6P0N20	5K6P0N25	5K6P0N30



Poly Angle 30° with Metal Box

DSDC1, 3, 6 shown



Metal Angle 30° with Metal Box (DSDC2 60°)

DSDC1, 3, 6 shown



DSDC9, 2 shown

SCAN ME >>>



BOXES

	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	1/2"	3/4"	1"	1 1/4"	1 1/2"	2"	2 1/2"
DSDC1	752C3N05	752C3N07	752C3N10	752C3N12	-	-	7K2C3N05	7K2C3N07	7K2C3N10	7K2C3N12	-	-	-
DSDC3	753C3N05	753C3N07	753C3N10	753C3N12	-	-	7K3C3N05	7K3C3N07	7K3C3N10	7K3C3N12	-	-	-
DSDC6	-	-	754C3N10	754C3N12	754C3N15	754C3N20	-	-	7K4C3N10	7K4C3N12	7K4C3N15	7K4C3N20	-
DSDC9	-	-	-	-	-	-	-	-	-	7K5C3N12	7K5C3N15	7K5C3N20	7K5C3N25
DSDC2	-	-	-	-	-	-	-	-	-	-	7K6C6N15	7K6C6N20	7K6C6N25



Poly Angle 70° with Larger Metal Wall Box with NPT



Metal Angle 70° with Metal Box with NPT

	1/2"	3/4"	1"	1 1/4"	1 1/2"	1"	1 1/4"	1 1/2"	2"	2 1/2"
DSDC1	752C7N05	752C7N07	752C7N10	752C7N12	752C7N15	DSDC6	7K4C7N10	7K4C7N12	7K4C7N15	7K4C7N20
DSDC3	753C7N05	753C7N07	753C7N10	753C7N12	753C7N15	DSDC9	-	7K5C7N12	7K5C7N15	7K5C7N20

ANGLES



POLY 30° ANGLE



METAL 30° ANGLE



METAL 70° ANGLE



METAL STRAIGHT ADAPTER

	POLY 30° ANGLE	METAL 30° ANGLE	METAL 70° ANGLE	METAL STRAIGHT ADAPTER
DSDC1	552M3	5K2M3	-	5K2M0
DSDC3	553M3	5K3M3	5K3M7	5K3M0
DSDC6	554M3	5K4M3	5K4M7	5K4M0
DSDC9	-	5K5M3	5K5M7	5K5M0
DSDC2	-	5K6M6 (60°)	-	5K6M0



* Set of Two (2)



For Inlets/Plugs Only



For Inlets/Plugs Only



MISC. ACCESSORIES

FINGER DRAWPLATES	PROTECTIVE INLET/PLUG CAP	PADLOCKABLE CAP ALUMINUM	CORD GRIP	RECEPTACLE LOCKING PIN
61-3A346	31-1A426	-	see pg 160	LP-843
61-6A346	31-3A426	-	see pg 160	LP-843
31-6A346	31-6A426	DS6MC	see pg 160	LP-843
**	31-9A426	DS9MC	see pg 160	LP-843
**	39-2A426	DS2MC	see pg 160	LP-843

* Recommended for facilitated mating.

** An easy closing mechanism is standard on DSDC9 and DSDC2.

! Accessories rated for hazardous locations are not returnable.