

DS30 Switch-Rated - 30 A

UL/CSA Ratings

- **Max Amperage & Voltage**
30 A, 600 VAC
- **Switch-Rating (AC Only)**
Branch Circuit & Motor Circuit
Disconnect Switching
- **Horsepower Ratings**

120 V	1Ø	1.5 hp
240 V	1Ø	3 hp
208 V	3Ø	5 hp
240 V	3Ø	5 hp
480 V	3Ø	15 hp
600 V	3Ø	15 hp
- **Short Circuit Rating**
100 kA Close & Withstand
Testing was performed with 125 A RK1 fast-acting Mersen fuses.
- **Environmental Ratings**
Type 3R (Standard)
Type 4X (Optional)
- **Temperature Range**
Min -40°F/Max 140°F
See pg 260 for temperatures outside of this range.
- **Wiring Capacity**
Based on THHN wire sizes.
Min 14 AWG Max 4 AWG
Aux Contacts: 14 AWG
- **Certifications**
UL 2682, UL 1682,
CSA C22.2 NO. 182.1, NOM

Receptacle (female)



Inlet (male)



! Remember to add installation accessories to your order

North American UL/CSA Configurations

VOLTAGE	POLARITY	PART # POLY	PART # POLY
120 V	1P+N+G	33-34165	33-38165
120 208 V	3P+N+G	33-34167	33-38167
125 V	1P+N+G	33-34075	33-38075
125 250 V	2P+N+G	33-34076	33-38076
208 V	2P+G	33-34162	33-38162
208 V	3P+G	33-34163	33-38163
250 V	2P+G	33-34072	33-38072
250 V	3P+G	33-34073	33-38073
277 V	1P+N+G	33-34045	33-38045
277 480 V	3P+N+G	33-34047	33-38047
347 600 V	3P+N+G	33-34147	33-38147
480 V	2P+G	33-34042	33-38042
480 V	3P+G	33-34043	33-38043
600 V	2P+G	33-34142	33-38142
600 V	3P+G	33-34143	33-38143

For international configurations and ratings (IEC, CE) visit meltric.com/international-catalog or contact Customer Service at 800-433-7642.

Main Options



Auxiliary/Pilot Contacts



Mushroom Pawl



Padlock Pawl



Self-Returning Lid

Recommended for cord applications to keep lid tucked in to avoid damage.

! See pages 237-246 for detailed information on these options

RECEPTACLE OPTIONS

SUFFIX

INLET OPTIONS

SUFFIX

With 2 Auxiliary/Pilot Contacts	Recept # -972	With 2 Auxiliary/Pilot Contacts	Inlet # -972
With 3 Auxiliary/Pilot Contacts	Recept # -973	With 3 Auxiliary/Pilot Contacts	Inlet # -973
With 4 Auxiliary/Pilot Contacts	Recept # -974	With 4 Auxiliary/Pilot Contacts	Inlet # -974
Type 4X & Self-Returning Lid	Recept # -4X	Type 4X Watertightness	Inlet # -4X
Straight Insertion	Recept # -352 ²	Self-Ejecting Plug Release**	Inlet # -338
Self-Ejecting Connector Release**	Recept # -354 ²	Without Lockout Hole	Inlet # -A155
Mushroom Pawl	Recept # -375	For Microswitch	Inlet # -270 ^{3,4}
Padlock Pawl	Recept # -843		
Screw-Type Locking Pawl	Recept # -845		
Metal Pawl (on Poly Receptacle)	Recept # -824		
Self-Returning Lid (Manual Close)	Recept # -NC		
With Microswitch	Recept # -270 ^{3,4}		

Notes:

** For self-ejecting connectors and plugs, a 443 suffix must be added to the handle part number. See pages 239-240 for more information.

² This option includes the Self-Returning Lid.

³ Not UL/CSA listed.

⁴ Not available on 3P+N+G configurations.

Order Example: 480 V DS30 + 2 auxiliary contacts
DS30 Poly inlet 3P+G = 33-38043-972



INSTALLATION ACCESSORIES – SIZE 3

When properly installed, all accessories meet or exceed the environmental ratings of the devices they are mounted to; unless otherwise noted.

HANDLES

HANDLE WITH NPT		PART # POLY	PART # METAL
	1/2"	513P0N05	593P0N05
	3/4"	513P0N07	593P0N07
	1"	513P0N10	593P0N10
	1 1/4"	513P0N12	593P0N12

For available cord grips, see pg 231.

POLY HANDLE WITH CORD GRIP		CABLE RANGE	PART #
		.520-.680"	713P0CP5
		.680-.980"	713P0DP4
		.980-1.260"	713P0EP4

METAL HANDLE WITH CORD GRIP		CABLE RANGE	PART #
		.635-.750"	793P0CS4
		.770-.850"	793P0DS1
		.875-1.000"	793P0DS3
		1.000-1.125"	793P0ES2

POLY HANDLE		CABLE RANGE	PART #
		.390-1.180"	513P0D30

POLY HANDLE WITH BUILT IN DRAWPLATES		CABLE RANGE	PART #
		.390-1.180"	513P0D30473

Makes connector closures easier.

POLY HANDLE WITH CLAMP & BUSHING		CABLE RANGE	PART #
		.750-.875"	713P0S14
		.875-1.000"	713P0S16
		1.000-1.125"	713P0S18
		1.125-1.250"	713P0S20
		1.250-1.375"	713P0S22

ANGLES

POLY ANGLE		ANGLE	PART #
	30°		513M3

	70°		513M7
---	-----	--	-------

Panel mounting only.

METAL ANGLE		ANGLE	PART #
	0°		593M0

	30°		593M3
---	-----	--	-------

	FS/FD 30°		793M3FS
---	-----------	--	---------

Base measures approximately 4.2" x 2.7". Due to the variation in sizes of FS boxes, please verify that your FS box matches our dimensions, if not call Customer Service for other solutions.

	70°		593M7
---	-----	--	-------

BOXES

POLY CONDUIT ENTRY WITH NPT			PART #
	30°	1/2"	513B3N05
	30°	3/4"	513B3N07
	30°	1"	513B3N10

* Interior volume with receptacle installed.

POLY WALL BOX WITH ANGLE		PART #
--------------------------	--	--------

	70°	513C7000
---	-----	----------

70° poly boxes are not drilled.

	Ground Bar	51AA089
---	------------	---------

* Interior volume with receptacle installed.

POLY ANGLE WITH METAL BOX WITH NPT			PART #
------------------------------------	--	--	--------

	70°	1/2"	713C7N05
	70°	3/4"	713C7N07
	70°	1"	713C7N10
	70°	1 1/4"	713C7N12
	70°	1 1/2"	713C7N15

* Interior volume with receptacle installed.

METAL BOX WITH NPT			PART #
--------------------	--	--	--------

	0°	1/2"	7T1F0N05
	0°	3/4"	7T1F0N07
	0°	1"	7T1F0N10
	0°	1 1/4"	7T1F0N12

POLY ANGLE WITH METAL BOX WITH NPT			PART #
------------------------------------	--	--	--------

	30°	1/2"	713C3N05
	30°	3/4"	713C3N07
	30°	1"	713C3N10
	30°	1 1/4"	713C3N12

* Interior volume with receptacle installed.

NPT on top or bottom (if rotated). For other configurations, contact Customer Service.

MISCELLANEOUS ACCESSORIES

FINGER DRAWPLATES	
-------------------	--

	61-6A346
---	----------

Set of Two (2)
Recommended for cord to cord assembly applications, for facilitated mating.

PROTECTIVE INLET/PLUG CAP	
---------------------------	--

	31-3A426
---	----------

For Inlets/Plugs Only.

PADLOCKABLE INLET/PLUG CAP	
----------------------------	--

	DS3PC
---	-------

For Inlets/Plugs Only.

SPRING-LOADED PADLOCKABLE INLET/PLUG CAP	
--	--

	31-3A226
---	----------

For Inlets/Plugs Only. In order to achieve max water ingress protection of Type 3R/IP55, spring loaded caps should be ordered with inlets equipped with -A155 suffix.

EASY RETROFIT ADAPTER PLATES	
------------------------------	--

	see pg 246
---	------------

Mount to existing boxes.

RECEPTACLE LOCKING PIN	
------------------------	--

	LP-843
---	--------

Requires Padlockable Pawl option (-843) on receptacle.