

Cable space door, 1800x600mm, 3mm double bit lock, Mild Steel, IP44

CATALOG NUMBER

DPA1806R5

The cabling door permits access to the individual cable space compartments, which allows for easy installation and maintenance in the field.



FEATURES

Description: To close a vertical cable section. Used in combination with CDV. In order to close the front, top and bottom panels DPC/DPCV are required.

Material: 2 mm steel plate.

Finish: RAL 7035 structured powder coating.

Protection: Complies with IP 44.

Mounting requirements: Add CDH for MC frames and use CDHK for MK frames.

Pack quantity: 1 door with hinges and equipped with double-bit 3 mm espagnolette locking system.

PRODUCT ATTRIBUTES

Height: 70.87in

Width: 23.62in

Enclosure Material: Mild Steel

Product Family: Free-Standing

Material: Mild Steel

Finish: Plated

Color: Light Gray

Color Code: RAL 7035

Thickness: 0.08in

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE