

Water-Cooled Indoor/Outdoor GW100 AC CR43WC, 8500BTU 230V, Brushed, SS304

Obsolete

CATALOG NUMBER

CR430826GW100



The Water-Cooled Indoor/Outdoor Air Conditioners remove heat from the system by means of the water cooling the refrigerant. No external air movers or condenser coils required which could get clogged. They have an attractive design with minimal use of visible fasteners including easy-mount flanges for simple installation.

INDUSTRY STANDARDS

UL/cUL Listed; Type 4; 4X optional; File No. SA6453

UR/cUR Recognized

UR/cUR Recognized on select models, reference performance data tables.

CE

EAC

FEATURES

Heat is removed from the system by means of the water cooling the refrigerant; no external air movers or condenser coils to get clogged

Attractive industrial design with minimal use of visible fasteners

Operating temperature range from 50 F/10 C to 125 F/52 C

Maximum water usage of 2 GPM at 90 F water intake temperature

Reliable mechanical thermostat located behind the front panel of the unit

Low-carbon mild-steel sheet-metal cover for rugged factory and outdoor environments

Easy-mount flanges for simple installation

Every unit functionally tested before shipping

Standard Indoor Air Conditioner models also include: Electro-Mechanical Thermostat, Surge Suppressor, Robust reciprocating compressor

Mounting hardware, gaskets and user manual furnished with the unit

PRODUCT ATTRIBUTES

Article Number: 22842
Nominal Capacity Watts: 2490W
Nominal Capacity Btu/h: 8500Btu/h
Nominal Voltage: 230V
Number of Phases: 1
Refrigerant: R134a
Material: Stainless Steel 304
Operating Temperature: 50 – 131°F
Remote Access Control: No
Outdoor Installation: Yes
Height: 43.31in
Width: 15.75in
Depth: 10.25in
Finish: Brushed #3
Weight: 166lb
Thickness: 16ga

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.



Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE