Industrial Workstation, 24.00x24.00x12.00, Lt Gray, Steel



CATALOG NUMBER

IWS242424DE1LG

A simple plug-and-play solution, the Industrial Workstation comes with vertical motion pendant arm and enclosure mounted on a pedestal with base for industrial environments. It accommodates mounting of a flat screen monitor with lift-off cover, keyboard, and mouse as well as PC protection. Display and keyboard can be raised and lowered with one hand. Keyboard folds up when not in use.

INDUSTRY STANDARDS

UL 508A Listed; Type 4, 12; File No. E61997

cUL Listed per CSA C22.2 No. 94; Type 4, 12; File No. E61997

Wall-mounting brackets required to maintain UL/CSA external mounting requirement.

NEMA/EEMAC Type 4, 12, 13

IP66

IEC 60529, IP66

FEATURES

Vertical motion pendant arm supports 6-15 lb. (3-7 kg) loads with an internal gas spring counterbalance
Provides 12-in. (305mm) vertical height adjustment
Toggle lever locks arm in place when repositioned vertically
3 x 3-in. and 4 x 4-in. VESA mounting patterns fit most flat screen monitors
Arm swivels 340 degrees at monitor end and 180 degrees at mounting end
Display tilts forward 15 degrees and back 45 degrees to reduce glare
Display and keyboard stay level as they travel vertically
Side cable manager protects cables and cords from pulling or chafing
Monitor shield with lift-off cover
Includes pedestal with base
Concept enclosure with quarter turn slotted latches and storage shelf
Integrated with power distribution, thermal management, network and power connector, USB 3.0 port, and cable entry

Monitor, keyboard and mouse are not included

USB 3.0 Type A receptacle to Type A plug

PRODUCT ATTRIBUTES

Article Number: 38436

Max Enclosure Size: 24.00 x 24.00 x 12.00in

Configuration: M12 4-pole Femaile to RJ45 Male Ethernet Receptacle

Power Source: 125V Duplex Receptable

Power Connector Type: Male 3-pole Receptacle

Cable Entry: 3 - 4 mm; 4 - 5 mm; 7 - 8 mm; 10 - 11 mm

Cable Entry Quantity: 4

Height: 67.58in

Width: 28.16in

Depth: 39.72in

Material: Mild Steel

Finish: Powder Coated

Color: Light Gray

Color Code: RAL 7035

Body Thickness: 14ga

Door Thickness: 16ga

Weight: 218lb

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.

This document is system-generated.