We connect and protect

RackPower PDU RP3000 208V 3PH / 30A, 21x C13 + 3x C19 L21-30P plug, Black, Steel

CATALOG NUMBER

RP30208P30AP324

RackPower Intelligent Power Distribution Units address controlling power on Cabinets as well as Open Frame Racks and Wall-Mount enclosures. Design your power solution using a variety of configuration options. The units are available in horizontal 19-in. rack or vertical mounting capabilities and a broad range of features.

If the portfolio of pre-configured items does not meet your needs, all PDUs can be configured to your specifications as a custom order. Contact Customer Service to place an order.

To configure a custom PDU, go to https://configurator.schroff.biz/PDU_Webapp/

INDUSTRY STANDARDS

Test to UL File E309439 UL 60950-1 Information Technology Equipment

Test to cUL File E309439 CSA-C22.2 No. 60950-1 Information Technology Equipment

Technology Equipment

FCC

CE

RoHS

REACH

FEATURES

Single or multi-phase
Input voltages North American 110 / 120 VAC or 208 VAC, European and Asia 230 VAC or 400 VAC
Global plug and receptacles NEMA and IEC rated
5 Configuration types: RP3000, RP2000, RP1500, RP1000, RP100
External communications and monitoring – protected and secure LAN connections
Local and remote power monitoring of single outlets and circuits showing data for current (AMP), voltage (Volt), power (kW), energy consumption (kWh) and power factor of entire PDU with a metering accuracy to within +/- 1%

Remote power on/off switch
Field replaceable, “hot-swappable”, smart monitor (RP Meter) and DC module
19-in. Rack Mounting (1 and 2 RU offering)
Versatile vertical / rack and cabinet mounting
Surge protection
Dual power feed entry for single phase RackPower PDUs
Temperature Sensor or Temperature and Humidity Sensor
Power cord whip – various lengths, colors and plugs
Various cord length and plug styles available; also available in LSZH (low smoke zero halogen)
Mounting hardware included

PRODUCT ATTRIBUTES

Article Number: 38761
Height: 67in
Width: 3in
Depth: 2in
Material: Mild Steel
Finish: Powder Coated
Color Code: RAL 9005
Color: Jet Black
Electrical Load Rating: 30A
Voltage AC: 208V
Number of Phases: 3Ph
Socket Quantity: 24
Socket Type: (21) C13; (3) C19
Plug Type: NEMA L21-30P
Mounting: Vertical
Weight: 22lb

WARNING

nVent products shall be installed and used only as indicated in nVent's product instruction sheets and training materials. Instruction sheets are available at www.nvent.com and from your nVent customer service representative. Improper installation, misuse, misapplication or other failure to completely follow nVent's instructions and warnings may cause product malfunction, property damage, serious bodily injury and death and/or void your warranty.

Our powerful portfolio of brands:

CADDY ERICO HOFFMAN ILSCO SCHROFF TRACHTE

©2026 nVent. All nVent marks and logos are owned or licensed by nVent Services GmbH or its affiliates. All other trademarks are the property of their respective owners. nVent reserves the right to change specifications without notice.