



Model Number CB3-AL-TF-56C-2-B-D-1.5-230|460-60

MFG PN T56 1.5U2B

List Price --

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data		General Data	
Rated Motor Output Power	1.5 HP	Frame Size	56
Rated Motor Speed	3500 r/min	Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ	Approximate Weight	24
Rated Motor Current	3.9/1.95 Amps	NEMA Design	B
Service Factor	1.25	IP Rating	55
KVA Code	M	Insulation Class	F
Nominal Efficiency	84 %	Tropicalization	YES
Nominal Power Factor	0.84 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	40.5	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	
Locked Rotor	-	316	19	40	
Breakdown	-	372	-	Rated Altitude (M)	
Pull Up	-	269	-	1000	
125% of FL	3483	-	2.35	Coating	
75% of FL	3534	-	1.59	7024 - Graphite Grey	
50% of FL	3557	-	1.29	Shaft Grounding	
No Load		-	0.99	YES	
				Mechanical Data	
				Bearing DE Side	6204 ZZ
				Bearing NDE Side	6204 ZZ
				Moment of Inertia	kg.m2
				Noise Level	Per NEMA dB (A)

Hazardous Location	Class 1, Div2 Grp A,B,C, D				
--------------------	----------------------------	--	--	--	--

CT VFD Range		--	Loaded Torque Curves	
			P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor	

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A



Wiring Diagram	3PH 9 Lead Dual Voltage
----------------	-------------------------

3 Phase - YY/Y - 9 Lead

4,1 Blue / 5,2 White / 6,3 Org / 7 Yl / 8 Blk / 9 RD

Cast Iron- 1,2,3 Top - 4,5,6,7,8,9 Bottom

Aluminum - 4,5,6,8,9 Top - 1,2,3,7 Bottom



FRAME: 56C

HP:

RPM:

PHASE: 3

VOLT: 230/460V

ENCL: TEFC

FREQ: 60 Hz

FLA:

LRA:

