



Model Number CB3-AL-TF-56C-2-B-D-1-230|460-60

MFG PN T56 1U2B

List Price --

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data

General Data

Rated Motor Output Power	1 HP	Frame Size	56
Rated Motor Speed	3490 r/min	Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ	Approximate Weight	18
Rated Motor Current	3.1/1.55 Amps	NEMA Design	B
Service Factor	1.25	IP Rating	55
KVA Code	K	Insulation Class	F
Nominal Efficiency	79 %	Tropicalization	YES
Nominal Power Factor	0.77 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	2.07 Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	53.4	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	310	11.3	Rated Altitude (M)	1000
Breakdown	-	316	-	Coating	7024 - Graphite Grey
Pull Up	-	217	-	Shaft Grounding	YES
125% of FL	3464	-	1.77	Brake Voltage (DC)	
75% of FL	3525	-	1.32	Brake Torque (N-M)	
50% of FL	3550	-	1.17	Mechanical Data	
No Load		-	1.1		

Hazardous Location	Class 1, Div2 Grp A,B,C, D			Bearing DE Side	6204 ZZ
				Bearing NDE Side	6204 ZZ
				Moment of Inertia	kg.m2
				Noise Level	Per NEMA dB (A)

CT VFD Range	--	Loaded Torque Curves	--
P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor			

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A
Wiring Diagram	3PH 9 Lead Dual Voltage		



3 Phase - YY/Y - 9 Lead

4,1 Blue / 5,2 White / 6,3 Org / 7 Yl / 8 Blk / 9 RD

Cast Iron- 1,2,3 Top - 4,5,6,7,8,9 Bottom

Aluminum - 4,5,6,8,9 Top - 1,2,3,7 Bottom

CONNECTIONS



Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540

FRAME: 56C

HP:

RPM:

PHASE: 3

VOLT: 230/460V

ENCL: TEFC

FREQ: 60 Hz

FLA:

LRA:

