



Model Number GR3-CI-TF-184T-6-B-D-2-230|460-60

MFG PN TFC184T2U6B

List Price --

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data		General Data	
Rated Motor Output Power	2 HP	Frame Size	184
Rated Motor Speed	1175 r/min	Enclosure	TEFC
Rated Motor Voltage (3 Phase)	230 460-60 Volts - HZ	Approximate Weight	112.2
Rated Motor Current	6.2/3.1 Amps	NEMA Design	BE
Service Factor	1.25	IP Rating	55
KVA Code	L	Insulation Class	F
Nominal Efficiency	88.5 %	Tropicalization	YES
Nominal Power Factor	0.68 cosθ	Duty	Cont.
Full Load Torque Ft-Lb	9.042976 Ft-Lb	Cable Entry	1.25
Temp Rise @ Full Load °C	25.9	Feet Removable	YES
Efficiency Level	IE3 - NEMA Premium	Double Drilled	NO

Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	
Locked Rotor	-	270	22.63	Rated Altitude (M)	1000
Breakdown	-	346	-	Coating	7024 - Graphite Grey
Pull Up	-	207	-	Shaft Grounding	NO
125% of FL	1172	-	3.5	Brake Voltage (DC)	
75% of FL	1185	-	2.65	Brake Torque (N-M)	
50% of FL	1190	-	2.3	Mechanical Data	
No Load	1198	-	1.99	Bearing DE Side	6306 ZZ

Hazardous Location	Class 1, Div 2, Grp A,B,C,D		Bearing NDE Side	6306 ZZ
			Moment of Inertia	kg.m2
			Noise Level	Per NEMA dB (A)

CT VFD Range	--	Loaded Torque Curves	--
		P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), $\cos\phi$ = Power Factor	

Certifications	UL	CSA	DOE
File Numbers	323353	224693	096A

Wiring Diagram	3PH 9 Lead Dual Voltage
----------------	-------------------------



3 Phase - YY/Y - 9 Lead

4,1 Blue / 5,2 White / 6,3 Org / 7 Yl / 8 Blk / 9 RD

Cast Iron- 1,2,3 Top - 4,5,6,7,8,9 Bottom

Aluminum - 4,5,6,8,9 Top - 1,2,3,7 Bottom

CONNECTIONS



FRAME: 184T HP: RPM: PHASE: 3 VOLT: 208 - 230/460V ENCL: TEFC FREQ: 60 Hz FLA: LRA:

