






Model Number	XR3-CI-TF-160LB3-2-BR-D-25-190 380-50
MFG PN	T 160L1-2
List Price	--

All data shown at HIGH voltage setting

Format STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power		25 HP		Frame Size	160
Rated Motor Speed		2940 r/min		Enclosure	TEFC
Rated Motor Voltage (3 Phase)		190 380-50 Volts - HZ		Approximate Weight	372.4
Rated Motor Current		66.6/33.3 Amps		NEMA Design	BE
Service Factor		1		IP Rating	55
KVA Code		H		Insulation Class	H
Nominal Efficiency		92.4 %		Tropicalization	YES
Nominal Power Factor		0.921 cosθ		Duty	Cont.
Full Load Torque Ft-Lb		44.256 Ft-Lb		Cable Entry	M32 X 1.5
Temp Rise @ Full Load °C		86.8		Feet Removable	YES
Efficiency Level		IE3 - NEMA Premium		Double Drilled	YES
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	203	248	Rated Altitude (M)	1000
Breakdown	-	298	-	Coating	7024 - Graphite Grey
Pull Up	-	157	-	Shaft Grounding	YES
125% of FL	2917	-	42.37	Brake Voltage (DC)	--
75% of FL	2956	-	25	Brake Torque (N-M)	--
50% of FL	2972	-	17.52	Mechanical Data	
No Load	2997	-	7.54	Bearing DE Side	6309 C3
Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Bearing NDE Side	6309 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)
CT VFD Range		--		Loaded Torque Curves	--
		P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor			
Certifications	UL	CSA	DOE		
File Numbers	323353	224693	096A		
Wiring Diagram	3PH 12 Lead IEC Dual Voltage				



MODEL NUMBER	XR-160LB3-CI- TF	ISSUE DATE:	05/2025
DIMENSIONS	in		
CASTING MATERIAL	CAST IRON	WWW.TECHTOPIND.COM	

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540