




Model Number	XR3-CI-TF-160MB35-2-BR-D-15-190 380-50
MFG PN	T 160M1-2
List Price	--

All data shown at HIGH voltage setting

Format | STD 3 Phase

Electrical Data				General Data	
Rated Motor Output Power		15 HP		Frame Size	160
Rated Motor Speed		2940 r/min		Enclosure	TEFC
Rated Motor Voltage (3 Phase)		190 380-50 Volts - HZ		Approximate Weight	277.8
Rated Motor Current		40/20 Amps		NEMA Design	BE
Service Factor		1		IP Rating	55
KVA Code		H		Insulation Class	H
Nominal Efficiency		91.2 %		Tropicalization	YES
Nominal Power Factor		0.93 cosθ		Duty	Cont.
Full Load Torque Ft-Lb		26.170048 Ft-Lb		Cable Entry	M32 X 1.5
Temp Rise @ Full Load °C		53.7		Feet Removable	YES
Efficiency Level		IE3 - NEMA Premium		Double Drilled	NO
Load Data	RPM	Trq %FL	Current Amps	Rated Ambient (°C)	40
Locked Rotor	-	182	148.7	Rated Altitude (M)	1000
Breakdown	-	270	-	Coating	7024 - Graphite Grey
Pull Up	-	162	-	Shaft Grounding	YES
125% of FL	2929	-	25.19	Brake Voltage (DC)	--
75% of FL	2961	-	15	Brake Torque (N-M)	--
50% of FL	2975	-	10.62	Mechanical Data	
No Load	--	-	4.84	Bearing DE Side	6309 C3
Hazardous Location	Class 1, Div 2, Grp A,B,C,D			Bearing NDE Side	6309 C3
				Moment of Inertia	-- kg.m2
				Noise Level	Per NEMA dB (A)
CT VFD Range		--	Loaded Torque Curves		--
			P1 = INPUT POWER (KW), S = Slip (% of Sync RPM), η = Efficiency (%), cosφ = Power Factor		
Certifications	UL	CSA	DOE		
File Numbers	323353	224693	096A		
Wiring Diagram	3PH 12 Lead IEC Dual Voltage				



MODEL NUMBER	XR-160MB35-CI-TF	ISSUE DATE:	05/2025
DIMENSIONS	in		
CASTING MATERIAL	CAST IRON	WWW.TECHTOPIND.COM	

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540

Techtop Industries -2815 Colonnades Court - Peachtree Corners, GA 30071 - Phone: (678) 436-5540